



Superior  
Manufacturing  
Group, Inc.

# 190 BrilliantStep™ ImageMatting Specifications

## Specialty



**B**rilliantStep™ imagematting is printed with a patented dye-injection process for long lasting, vibrant color. Advanced design capabilities like custom borders, background designs, and an enhanced color palette of 189 base colors, adds punch to your message.

Dye Process	Dye Injection
Antistatic	Yes
Carpet Pile (oz/yd <sup>2</sup> )	24
Mat Sizes	2' x 3' (22" x 33"), 2.5' x 3' (27" x 33"), 3' x 4' (33" x 45"), 3' x 5' (33" x 57"), 3' x 6' (33" x 68"), 3' x 10' (33" x 115"), 4' x 6' (45" x 68"), 4' x 8' (45" x 91"), 4' x 10' (45" x 115"), 4' x 12' (45" x 139"), 5' x 8' (57" x 91"), 5' x 10' (57" x 115"), 5' x 12' (57" x 139"), 5' x 20' (57" x 230")
Mat Weight	Approximately .5 lbs per square ft.
Flammability Test (DOC FF1-70)	Pass
Flammability Test (DOC FF2-70)	Pass
Launderable	Yes
Mat Profile	0.33"

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



- Face Fiber: Nylon 6,6
- Border Width: 5/8"
- Rubber Polymer Type: Nitrile
- Custom sizes available up to 10" wide - Mats up to 5' wide, unlimited length - Mats 6' - 10' wide can be a maximum of 24' long
- Color Palette: 189 base colors
- Custom Borders: 11
- Background Designs: 10



Logo Friendly

